

Acuity 18 (enflufocon A)

Print Date: 01/17 Enflu-Rev001

Indications	Characteristics		Lens Parameters	
<ul style="list-style-type: none"> • Myopia • Hyperopia • Astigmatism • Presbyopia • Keratoconus • Pellucid Marginal Degeneration • Post Penetrating Keratoplasty • Post RK • Post Lasik 	Oxygen Permeability (Dk*)	21	Chord Diameter Range	7.0 to 21.0mm
	Refractive Index	1.445	Center Thickness Range	0.07 to 0.65mm
	Hardness (Shore D)	84	Base Curve Range	4.00 to 11.50mm
	Specific Gravity	1.22	Power Range	-20.00 to +20.00D
	Wetting Angle**	88/25	Add Powers	+1.00 to +4.00D
	Light Transmittance*** [Average %T (380-780nm)]	81	Water Content	< 1%
	<small>*ISO/Fatt Method: DKUnits=$\times 10^{-11}$ (cm³ O₂)(cm)/[(sec)(cm²)(mmHg)]@35°C; **Sessile Drop per ANSI Z80.20, 8.11; ***ISO8599:1994</small>			

Available Tints	Standard Diameter			
	Blue	Green	Ice Blue	Grey
ACUITY 18 (enflufocon A)	✓	✓	✓	✓



1-888-POLYMER • www.acuitypolymers.com

Acuity Polymers, Inc. | 1667 Lake Avenue, Building 59, Suite 303 | Rochester, NY 14615, USA